



CARE . TRUST . RESPONSIBILITY

# KB-68/KB-78H PROGRAMMABLE KEYBOARD

## DURABLE AND DEPENDABLE KEYBOARD



### KB-68 Architect Great POS Experiences with Ease

Partner Tech knows you need technology that helps you provide fast, efficient customer service. The Partner Tech KB-68 Programmable Keyboard is a high-quality, durable 68-key keyboard that makes key programming easy so you can architect quick, convenient checkout experiences.

### KB-78H Dependable, Easy-to-Use POS Utility

The last touchpoint with customers is at the checkout, and you want that experience to create a good lasting impression of your brand. The Partner Tech KB-78H programmable keyboard enables your staff to quickly and accurately input POS data and provide great customer service.

#### KB-68 SPECIAL FEATURES

- All fully programmable and relegendable keys
- PS2 interface

#### OPTIONAL

- 3-track MSR
- USB interface
- 6 position programmable key lock
- Spill resistant membrane key switch

#### KB-78H SPECIAL FEATURES

- All fully programmable and relegendable keys
- USB interface
- Supports OPOS

#### OPTIONAL

- 3-track MSR
- 6 position programmable key lock
- Spill resistant membrane key switch

**KB-68/KB-78H PROGRAMMABLE KEYBOARD**

Item	KB-68
Number of key	68 keys
Key switch	Spill resistant membrane key switch
System LED	Layer, Num lock, Shift lock, Scroll lock
Interface	PS2 keyboard port USB keyboard for USB 1.1 (The I button and fingerprint mode USB interface only)
Software Support	OPOS, Java POS, Linux, Setup utility, I button setup, Fingerprint setup
Options	6 position key lock Magnetic card reader with single/dual/three tracks for ISO or JIS I/II IC card reader with PC/SC, EMV 2000 RFID work frequency AM125 KHz, read distance 6-8mm, 15 type dallas key readable I Button Fingerprint with resolution 500dpi, sensor size 7.2x7.2mm, dot matrix 128x128dots
Dimension	12.91in (L) x 5.94in (W) x 1.5 in(H) 13.78 in (L) x 5.94 in (W) x 1.5 in(H) with MSR
Certification	CE, FCC, BSMI, VCCI

Item	KB-78H
Number of key	78 keys
MSR (Option)	Triple Track
Keylock	6 steps keylock Each step can be programmed as a normal key Life cycle >= 25,000 times With clear step rotation
Power supply	PS/2: +5V/DC +10% USB: +5V/DC +5%
Current input	PS/2: <100mA USB: <100mA
Storage Temperature	104°F to 140°F
Operating Temperature	32°F to 122°F
Operating humidity	20% to 90%
Dimension	12.91in (L) x 5.94in (W) x 1.5 in(H) 13.78 in (L) x 5.94 in (W) x 1.5 in(H) with MSR

\*Specification is subject to change without prior notice



**PARTNER TECH USA INC.**  
15320 Barranca Parkway Suite 150.  
Irvine, CA 92618  
TEL: +1-949-598-1888  
sales@partnertechcorp.com

